



RoHS  
COMPLIANT



SURFACE PREPARATION PRODUCTS

# VpCI<sup>®</sup>-416

## DESCRIPTION

VpCI-416 is a heavy-duty water-based alkaline cleaner and degreaser offering unique flash corrosion protection. VpCI-416 can provide corrosion protection for up to 6 months during indoor storage. VpCI-416 is formulated to meet the requirements for cleaning and corrosion protection of parts and storage equipment. VpCI-416 penetrates to remove greases and oil deposits from machinery, engines, vehicles, construction equipment, and cranes in either industrial or marine applications.

The compounds contained in VpCI-416 function by altering hydrocarbons so that the deposits can be removed with water. VpCI-416 can be metered into power washers, steam cleaners, dip tanks, and other cleaning equipment. Along with good detergent properties, VpCI-416 is hard water stable.

While most cleaning compounds available on the market today are simple blends of surfactants and detergents which limit their cleaning effectiveness, VpCI-416 offers improved cleaning plus multimetal corrosion protection action in one step, resulting in significant savings. VpCI-416 has the unique ability to remove such deposits as heavy hydrocarbons, grease, drawing and buffing compounds, and machinery compounds.

## FEATURES

- Heavy-duty chemical cleaner and degreaser with unique cleaning action for removing hydrocarbon deposits
- Multimetal corrosion inhibitors leave a temporary protective coating, affording protection for a few months at 5% minimum concentration\*
- Provides exceptional resistance to pitting corrosion
- Non-toxic, non-corrosive, and does not contain nonylphenolethoxylates
- Provides excellent cleaning action at low temperatures
- Mild foaming
- Effective cleaner at low concentrations (1-3%)
- Exhibits hard water tolerance
- Formulation remains stable during freeze-thaw cycle
- Accepted by USDA for general cleaning in food plants (indirect contact with food)

\*The estimated time of protection may vary due to conditions.

## EFFECTIVE USES

- Machinery contaminated with oils
- Sheet metal coated with temporary protective oils or waxes prior to painting, pickling, or machining
- Metal parts contaminated with stamping, drawing, or buffing compounds
- Use as an effective additive for rinse tanks to improve protection for dry storage application (5-10% by weight)
- Multiple stage parts washers



## APPLICATION

VpCI-416 can be applied with any conventional equipment including sprayers, dipping tanks, steam cleaners, and power washers.

Heavy-duty Cleaning and Corrosion Protection:  
1 part VpCI-416 to 5-10 parts water.

Normal Cleaning (i.e. parts washing):  
1 part VpCI-416 to 10-40 parts water.

Light Cleaning (i.e. rinsing):  
1 part VpCI-416 to 40-150 parts water.

## PROPERTIES

|                      |                                 |
|----------------------|---------------------------------|
| Appearance           | Slightly hazy yellow liquid     |
| Exposure Time        | 20 seconds to 5 minutes         |
| pH                   | 12-12.7(Neat)                   |
| Density              | 8.6-8.8 lb/gal (1.03-1.05 kg/l) |
| Temperature Range    | 50°-300°F (10°-149°C)           |
| Non-volatile Content | 18-23%                          |

## PACKAGING

VpCI-416 is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes, and bulk.

## FOR INDUSTRIAL USE ONLY

**KEEP OUT OF REACH OF CHILDREN**

**KEEP CONTAINER TIGHTLY CLOSED**

**NOT FOR INTERNAL CONSUMPTION**

**CONSULT SAFETY DATA SHEET FOR MORE**

**INFORMATION**

### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer

Revised: 3/4/14, Cortec Corporation 1998-2014. All rights reserved. Supersedes: 10/14/11.  
© 2014, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.